


## ■ 東芝照明器具配光データシート

名称	東芝LED器具
形名	LEKT215163N-LD9



効	F 半	0 %
率	F 半	100 %
	F 全	100 %
器具光束		1530 lm

保守率	良	0.81
	中	0.77
	否	0.68

前面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

備考

光度 (cd/1000lm)				反射率 (%)	天井		80			70			50			30		20		0				
$\theta \setminus \phi$	A-A	B-B	C-C		壁	70	50	30	70	50	30	50	30	50	30	30	10	0	10	0				
0°	344	344	344		床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
10°	337	337	336	室指数 固有照明率 (×0.01)																				
20°	319	318	318	0.60	62	57	48	46	39	38	60	56	47	45	39	38	46	44	38	37	38	37	32	31
30°	293	288	289	0.80	75	68	60	57	51	49	72	66	59	56	50	49	57	54	49	48	48	47	43	41
40°	257	249	252	1.00	82	73	68	63	58	55	79	72	66	62	58	55	64	60	56	54	55	53	49	47
50°	215	203	207	1.25	90	80	76	70	67	63	87	78	75	69	66	62	71	67	64	61	62	60	56	53
60°	164	152	158	1.50	95	83	82	75	73	68	92	82	80	74	72	67	77	72	69	66	67	65	61	58
70°	102	96	102	2.00	103	90	92	82	84	77	100	88	90	81	82	76	85	79	79	74	76	73	69	67
80°	27	37	39	2.50	108	93	98	87	91	82	104	91	96	86	88	81	90	84	85	79	81	78	74	72
90°	0	2	2	3.00	112	96	103	90	96	86	108	94	100	89	94	85	94	87	89	83	85	82	78	76
100°	0	1	1	4.00	116	99	109	95	103	91	112	97	106	93	101	90	100	91	95	88	91	86	83	81
110°	0	1	1	5.00	119	101	113	97	108	94	115	99	110	96	105	93	103	94	99	91	94	89	87	84
120°	0	1	1	10.00	125	104	122	103	119	101	120	103	117	101	115	100	110	99	108	98	101	96	94	92
130°	0	1	1																					
140°	0	1	1																					
150°	0	1	1																					
160°	0	1	0																					
170°	1	1	1																					
180°	1	1	1																					

