

屋内照明器具特性

品番 (品名)	XLX230AENJ									
光源	LED5000_85_3200 x1 3200.0 lm									
管理番号	K0128261 (*) DB 1									
BZ分類	BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	4 %																			
下方光束	96 %																			
室指数	照明率 (X0.01)																		ZCM	
保守率	良 0.83 中 0.81 否 0.77	0.6	55	42	34	29	53	41	34	28	50	40	33	28	48	39	32	28	25	
		0.8	64	53	44	38	63	52	44	38	59	50	43	38	56	48	42	37	35	
		1.0	71	60	52	46	69	59	51	45	65	56	50	45	62	54	49	44	41	
		1.25	77	67	59	53	75	65	58	52	71	63	57	52	68	61	55	51	48	
下方投影面積 等価発光面積	c m ²	1.5	81	72	64	58	79	70	63	58	75	68	62	57	71	65	60	56	53	
		2.0	87	79	72	67	85	77	71	66	81	74	69	65	77	72	67	63	60	
		2.5	90	83	77	72	88	82	76	72	84	79	74	70	81	76	72	69	65	
取付高さ	器具間隔最大限		3.0	93	87	81	77	91	85	80	76	87	82	78	74	83	79	76	73	69
	横方向 (A)	縦方向 (B)																		
1.5m	1.96 m	1.98 m	4.0	96	91	87	83	94	90	85	82	90	86	83	80	87	83	81	78	74
2	2.61	2.6	5.0	98	94	90	87	96	92	89	86	92	89	86	83	89	86	84	81	78
2.5	3.25	3.22	7.0	101	97	94	92	99	96	93	90	95	93	90	88	92	89	88	86	82
3	3.91	3.85	10.0	102	100	98	96	101	98	96	94	97	95	93	92	94	92	91	89	85

